

6225/6225A

SOFT SERVE FREEZER

Two Flavor, Countertop, Digital Control A: Pump Feed Model









Simple But Powerful

Classy design that offers quality and simplicity

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

Self Closing Dispensing Valve

Automatically prevents product overflow after dispense

Dispense Speed Control

Provides flexibility in dispense rate control for different applications

Ideal for medium capacity outlets to add soft serve ice cream and frozen yogurt. Low profile design keeps operation simple and helps reduce cost of ownership.

Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight

Safety Protections


- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- $\bullet \ \ \mathsf{High}\,\mathsf{pressure}\,\mathsf{switch}\,\mathsf{to}\,\mathsf{prevent}\,\mathsf{compressor}\,\mathsf{overheating}$
- Thermal overload to protect from motor overheating






6225 / 6225A

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	2 + Twist
Freezing Cylinders	2 x 1.7 L / 1.8 qt
Mix Hoppers	2 x 12 L (8 L for A)
Output Capacity (80 g)	400 serves/hr
Clearance Requirements	152 mm/6" on left

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	139 / 306	164 / 362
Shipping	152 / 335	177 / 390

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	552 / 21.7	610 / 24.0
Depth	652 / 25.7	780 / 30.7
Height	977 / 38.5	1100 / 43.3
Volume	0.52 CBM / 18.48 CBF	

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	2.9	16	25
208-230/60/1	3.2	17	25

FEATURES	
Control Systems	Single, Digital
Refrigerated Hoppers	
Hopper Agitator	\checkmark
Temperature Display	
Standby Mode	
Auto Clsoing Dispensing Valves	
Dispensing Speed Control	\checkmark
Low Mix Indicator Light	
Low Mix Indicator Alarm	\checkmark
Low Temperature Protection	
Motor Amperage Protection	\checkmark
High Pressure Protection	
Thermal Overload Protection	\checkmark

AVAILABLE OPTIONS

Water Cooled	\checkmark
Top Air Discharge Chute	

 $[\]boldsymbol{\cdot}$ Above specifications are subject to change without notice