

# 6250/6250A

## SOFTSERVEFREEZER

Two Flavor, Floor, Digital Controls



### **Powerful & Versatile** Two-flavor medium capacity floor model for ice cream, frozen yogurt and much more

#### Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

#### **Digital Control and Display**

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

#### Low Mix Indicator

 ${\tt Light turns"ON" at low mix to alert operator to add mix}$ 

#### Self Closing Dispensing Valve

Automatically prevents product overflow after dispense

#### **Dispense Speed Control**

Provides flexibility in dispense rate control for different applications

Ideal for any medium capacity outlets to serve

soft ice cream, frozen yogurt, gelato or sorbet.

Fully loaded with all standard options.

#### **Hopper Agitators**

Maintain product consistency and prevent product separation

#### Auto Programming

Allows automatic switching of operation modes based on preset schedules

#### Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight

#### **Safety Protections**

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating




#### SPACEMAN ICE SYSTEMS (HK) CO, LIMITED

FACTORY: 1 GUANZE RD, INDUSTRY PARK, DAIXI TOWN, HUZHOU, ZHEJIANG, CHINA 313023 PHONE: +86 572 3826788 FAX: +86 572 3826755 Email: info@spaceman-company.com www.spaceman-company.com



## 6250 / 6250A

### SOFTSERVEFREEZER




#### SPECIFICATIONS

Flavors	2 + Twist
Freezing Cylinders	2 x 1.7L / 1.8qt
Mix Hoppers	2 x 12L / 12.7qt
Output Capacity (80 grams)	450 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)	
Net	180/400	190 / 422	
Shipping	195/433	205/456	
Volume	0.90 CBM / 31.78 CBF		

Dimensions	Net (mm/in)		Shipping (mm/in)
Width	552 / 21.7		660/26.0
Depth	652/25.7		830 / 32.7
Height	1474 / 58.0		1640 / 64.6
Electrical	MFS	MCA	Power(kW)
220-240/50/1	30	20	3.0
208-230/60/1	30	22	3.0

• Above specifications are subject to change without notice



FEATURES	
Control Systems	Two, Digital
Refrigerated Hoppers	
Hopper Agitator	
Temperature Display	
Standby Mode	
Auto Clsoing Dispensing Valves	
Dispensing Speed Control	
Low Mix Indicator Light	
Low Mix Indicator Alarm	
Low Temperature Protection	
Motor Amperage Protection	$\checkmark$
High Pressure Protection	
Thermal Overload Protection	$\checkmark$
<b>AVAILABLE OPTIONS</b>	
Water Cooled	$\checkmark$
Top Air Discharge Chute	
Spinner	$\checkmark$
Soft Start	
Custom Branding	$\checkmark$

#### SPACEMAN USA

224 Commerce St. Unit A1, Broomfield, CO 80020 PHONE: +01 720-328-1020 FAX: +01 720-528-8113 Email: sales@spacemanusa.com www.spacemanusa.com