

# 6240/6240A

### **SOFT SERVE FREEZER**

Two Flavor, Floor, Digital Control A: Pump Feed Model











## Simple But Powerful

Classy design that offers quality and simplicity

#### **Fast Freeze Down**

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

#### **Digital Control and Display**

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

#### **Low Mix Indicator**

Light turns "ON" at low mix to alert operator to add mix

#### **Self Closing Dispensing Valve**

Automatically prevents product overflow after dispense

#### **Dispense Speed Control**

Provides flexibility in dispense rate control for different applications

Ideal for medium capacity outlets to add soft serve ice cream and frozen yogurt. Low profile design keeps operation simple and helps reduce cost of ownership.

#### Standby

Maintains product temperature in both mix hopper and freezing cylinder below  $4.4^{\circ}\text{C}$  ( $40^{\circ}\text{F}$ ) overnight

#### **Safety Protections**


- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- $\bullet \ \ \mathsf{High}\,\mathsf{pressure}\,\mathsf{switch}\,\mathsf{to}\,\mathsf{prevent}\,\mathsf{compressor}\,\mathsf{overheating}$
- Thermal overload to protect from motor overheating






## 6240 / 6240A

## **SOFT SERVE FREEZER**





#### **SPECIFICATIONS**

Flavors	2 + Twist
Freezing Cylinders	2 x 1.7L / 1.8qt
Mix Hoppers	$2 \times 12 L (8 L for A)$
Output Capacity (80 grams)	400 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	165 / 364	175 / 386
Shipping	180/397	190 / 419
Volume	0.87 CBM / 30.7 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	552 / 21.7	650/25.6
Depth	652 / 25.7	820 / 32.3
Height	1474 / 58.0	1640 / 64.6

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	2.9	15	25
208-230/60/1	3.2	16	25

FEATURES	
Control Systems	Single, Digital
Refrigerated Hoppers	
Hopper Agitator	<b>~</b>
Temperature Display	
Standby Mode	$\checkmark$
Auto Clsoing Dispensing Valves	
Dispensing Speed Control	$\checkmark$
Low Mix Indicator Light	
Low Mix Indicator Alarm	$\checkmark$
Low Temperature Protection	
Motor Amperage Protection	$\checkmark$
High Pressure Protection	
Thermal Overload Protection	
AVAILABLE OPTIONS	
Water Cooled	$\checkmark$
Top Air Discharge Chute	

<sup>·</sup> Above specifications are subject to change without notice