

6265

## **SOFT SERVE FREEZER**

Three Flavor, Countertop, Digital Controls











### Powerful & Versatile

Most compact three-flavor counter model to serve ice cream and frozen yogurt

#### Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

#### **Digital Control and Display**

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

#### Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

#### **Self Closing Dispensing Valve**

Automatically prevents product overflow after dispense

#### **Dispense Speed Control**

Provides flexibility in dispense rate control for different applications

Ideal for medium capacity outlets with limited space to serve more flavor varieties of ice cream, frozen yogurt, gelato or sorbet. Fully loaded with all standard options.

#### **Hopper Agitators**

Maintain product consistency and prevent product separation

#### **Auto Programming**

Allows automatic switching of operation modes based on preset schedules

#### Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight

#### **Safety Protections**


- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- $\bullet \ \ \mathsf{High}\,\mathsf{pressure}\,\mathsf{switch}\,\mathsf{to}\,\mathsf{prevent}\,\mathsf{compressor}\,\mathsf{overheating}$
- Thermal overload to protect from motor overheating






# 6265

## **SOFT SERVE FREEZER**





#### **SPECIFICATIONS**

Flavors	3+2Twist
Freezing Cylinders	3 x 1.7L / 1.8qt
Mix Hoppers	3 x 8.0L / 8.5qt
Output Capacity (80 grams)	450 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/Ib (Gravity)	
Net	238 / 529	
Shipping	257 / 571	
Volume	0.78 CBM / 27.73 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	612 / 24.1	675 / 26.6
Depth	792 / 31.2	965/38.0
Height	1058 / 41.7	1205 / 47.4

Electrical	MFS	MCA	Power(kW)
220-240/50/1	30	24	4.3
208-230/60/1	30	26	4.3

• Above specifications are subject to change without notice

FEATURES	
Control Systems	Three, Digital
Refrigerated Hoppers	$\checkmark$
Hopper Agitator	$\checkmark$
Temperature Display	lacksquare
Standby Mode	$\checkmark$
Auto Clsoing Dispensing Valves	ightharpoons
Dispensing Speed Control	$\checkmark$
Low Mix Indicator Light	ightharpoons
Low Mix Indicator Alarm	$\checkmark$
Low Temperature Protection	
Motor Amperage Protection	$\checkmark$
High Pressure Protection	lacksquare
Thermal Overload Protection	$\checkmark$
AVAILABLE OPTIONS	
Water Cooled	ightharpoons
Top Air Discharge Chute	$ lap{}$
Spinner	$\checkmark$
Soft Start	
Custom Branding	$\checkmark$