

6336/6336A

SOFTSERVEFREEZER

Single Flavor, Floor, Digital Control







Powerful & Versatile

Most compact high capacity single flavor model to serve ice cream, frozen yogurt and much more

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Low Mix Indicator

 ${\tt Light turns"ON" at low mix to alert operator to add mix}$

Self Closing Dispensing Valve

Automatically prevents product overflow after dispense

Dispense Speed Control

Provides flexibility in dispense rate control for different applications

Ideal for high volume restaurants, fast food

chains and dessert stands to serve large crowds

ice cream, frozen yogurt, gelato or sorbet. Fully

loaded with all standard options.

SPACEMAN ICE SYSTEMS (HK) CO, LIMITED

FACTORY: 1 GUANZE RD, INDUSTRY PARK, DAIXI TOWN, HUZHOU, ZHEJIANG, CHINA 313023

Hopper Agitators

Maintain product consistency and prevent product separation

Auto Programming

Allows automatic switching of operation modes based on preset schedules

Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating




PHONE: +86 572 3826788 FAX: +86 572 3826755 Email: info@spaceman-company.com www.spaceman-company.com



6336 / 6336A

SOFTSERVEFREEZER



SPECIFICATIONS


Flavors	1
Freezing Cylinders	1 x 3.2L / 3.4qt
Mix Hoppers	1 x 15L / 15.9qt
Output Capacity (80 grams)	400 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	165/367	170 / 378
Shipping	180/400	185 / 411
Volume	0.88 CBM / 30.97 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	444 / 17.5	650/25.6
Depth	678 / 26.7	780/30.7
Height	1543 / 60.7	1730 / 68.1

Electrical	MFS	MCA	Power(kW)
220-240/50/1	20	16	2.5
208-230/60/1	25	18	2.5

· Above specifications are subject to change without notice



FEATURES	
Control Systems	One, Digital
Refrioerated Hoppers	
Hopper Agitator	
Temperature Display	
Standby Mode	
Auto Clsoing Dispensing Valves	
Dispensing Speed Control	
Low Mix Indicator Light	
Low Mix Indicator Alarm	
Low Temperature Protection	
Motor Amperage Protection	
High Pressure Protection	
Thermal Overload Protection	\checkmark
AVAILABLE OPTIONS	
Water cooled	
Top Air Discharge Chute	
Spinnor	
Soft Start	
Custom Branding	
Light Box	
Remote Auto Fill	

SPACEMAN USA

224 Commerce St. Unit A1, Broomfield, CO 80020 PHONE: +01 720-328-1020 FAX: +01 720-528-8113 Email: sales@spacemanusa.com www.spacemanusa.com