

6228B-C 6228AB-C

SOFT SERVE FREEZER

1 Flavor, Countertop, Pasteurization A: Pump Feed Model









Most Compact & Powerful medium capacity counter model with Auto-Pasteurization and intelligent control

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critical info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset schedules

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato but with desire for significant reduction in labor cost of cleaning.

Hopper Agitator

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- · High pressure switch to prevent compressor overheating

Refresh and Revive

Restore perfect consistency automatically to reduce product waste and labor cost while ensuring food safety

Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






6228B-C/6228AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	1
Freezing Cylinders	1 x 1.7L / 1.8qt
Mix Hoppers	1 x 12L (10L for A)
Output Capacity (80 grams)	360 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb(Gravity)	Kg/lb (Pump)
Net	119 / 262	124 / 273
Shipping	132 / 291	137 / 302
Volume	0.43 CBM / 15.21 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	384 / 15.1	500/19.7
Depth	720 / 28.3	870 / 34.3
Height	846 / 33.3	990/39.0

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	2.8	14	25
208-230/60/1	3.0	15	30

	FEATURES	
	Control System	Single, Digital
	Refrigerated Hopper	
	Hopper Agitator	\checkmark
	Temperature Display	
	Standby Mode	\checkmark
	Auto Closing Dispensing Valve	
	Dispensing Speed Control	\checkmark
	Low Mix Indicator Light & Alarm	
	Low Temperature Protection	ightharpoons
	Motor Overload Protection	
	High Pressure Protection	\checkmark
	Defrost & Refresh	
	Soft Start	\checkmark
	Direct Drive Pump	
	Auto-Pasteurization	

AVAILABLE OPTIONS	
Water Cooled	\checkmark
Top Air Discharge Chute	$\overline{\mathbf{v}}$

[·] Above specifications are subject to change without notice