

6236B-C 6236AB-C

SOFT SERVE FREEZER

1 Flavor, Countertop, Pasteurization A: Pump Feed Model









Most Compact & Powerful high capacity countertop model with Auto-Pasteurization and intelligent control

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset scheduels $\,$

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato with desire for significant reduction in labor cost of cleaning.

Hopper Agitator

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

Refresh and Revive

Restore perfect consistency automatically to reduce product waste and labor cost while ensuring food safety

Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






6236B-C/6236AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	1
Freezing Cylinders	1 x 3.2L / 3.4qt
Mix Hoppers	1 x 17L(12L for A)
Output Capacity (80 grams)	420 serves/hr
Clearance Requirements	152mm/6" on left

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	165/364	170 / 375
Shipping	181/399	186 / 410
Volume	0.47 CBM / 16.	62 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	454 / 17.9	500/19.7
Depth	681 / 26.8	870 / 34.3
Height	928 / 36.5	1080 / 42.5

Electrical	MFS	MCA	Power(kW)
380-415/50/3	15	11	2.9
208-230/60/3	20	18	3.1
208-230/50/1	25	16	2.3
208-230/60/1	30	18	2.5

 $[\]boldsymbol{\cdot}$ Above specifications are subject to change without notice

FEATURES	
Control System	Sinqle, Digital
Refrigerated Hopper	
Hopper Agitator	\checkmark
Temperature Display	
Standby Mode	\checkmark
Auto Closing Dispensing Valve	lacksquare
Dispensing Speed Control	\checkmark
Low Mix Indicator Light & Alarm	ightharpoons
Low Temperature Protection	\checkmark
Motor Overload Protection	ightharpoons
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	\checkmark
Direct Drive Pump	lacksquare
Auto-Pasteurization	\checkmark

AVAILABLE OPTIONS	
Water Cooled	$\overline{\mathbf{v}}$
Top Air Discharge Chute	
Cart (Trolley)	\checkmark