

6236B-C 6236AB-C

SOFT SERVE FREEZER

1 Flavor, Countertop, Pasteurization A: Pump Feed Model









Most Compact & Powerful high capacity countertop model with Auto-Pasteurization and intelligent control

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset scheduels $% \left(1\right) =\left(1\right) \left(1\right) \left($

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato with desire for significant reduction in labor cost of cleaning.

Hopper Agitator

Maintains product consistency and prevents product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

Refresh and Revive

Restore perfect consistency automatically to reduce product waste and labor cost while ensuring food safety

Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






6236B-C/6236AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	1
Freezing Cylinders	1 x 3.2 L / 3.4 qt
Mix Hoppers	1 x 19 L (13 L for A)
Output Capacity (80 g)	440 serves/hr
Clearance Requirements	152 mm/6" on left

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	156 / 344	165 / 364
Shipping	171 / 377	180 / 397

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	454 / 17.9	520 / 20.5
Depth	700 / 27.6	890 / 35.0
Height	994 / 39.1	1140 / 44.9
Volume	0.53 CBM / 18.63 CBF	

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
380-415/50/3	3.0	9	15
208-230/60/3	3.1	12	20

F	EA	UT	RI	ES

Control System	Single, Digital
Refrigerated Hopper	
Hopper Agitator	lacksquare
Temperature Display	
Standby Mode	lacksquare
Auto Closing Dispensing Valve	
Dispensing Speed Control	\checkmark
Low Mix Indicator Light & Alarm	
Low Temperature Protection	\checkmark
Motor Overload Protection	
High Pressure Protection	lacksquare
Defrost & Refresh	
Soft Start	ightharpoons
Auto-Pasteurization	

AVAILABLE OPTIONS

Water Cooled	\checkmark
Top Air Discharge Chute	

· Above specifications are subject to change without notice