

6378-C/6378A-C

SOFTSERVEFREEZER

Two Flavor, Floor, Digital Control A: Pump Feed Model



TF

Most **Powerful** and **Versatile** 2-flavor high capacity floor model for ice cream, frozen yogurt and much more

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Digital Control and Display

Digital control provides access to system settings and displays critical system information

Auto Programming

Allows automatic switching of operation modes based on preset schedules

Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight

Hopper Agitator

Maintain product consistency and prevent product separation

Ideal for high capacity outlets to serve ice cream, frozen yogurt, gelato or sorbet. Fully loaded with all standard options. Small footprint helps save floor space.

Soft System Start

Slow motor start reduces equipment noise and stress on drive train

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Quick Freeze

Turn on freeze immediately to freeze down to serving viscosity when quick service is required after long idle period

Self-closing Valve with Speed Control

Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control




SPACEMAN ICE SYSTEMS (HK) CO, LIMITED

FACTORY: 1 GUANZE RD, INDUSTRY PARK, DAIXI TOWN, HUZHOU, ZHEJIANG, CHINA 313023 PHONE: +86 572 3826788 FAX: +86 572 3826755 Email: info@spaceman-company.com www.spaceman-company.com



6378-C / 6378A-C

SOFT SERVE FREEZER



SPECIFICATIONS

Flavors	2 + Twist
Freezing Cylinders	2 x 3.2L / 3.4qt
Mix Hoppers	2 x 15L (10L for A)
Output Capacity (80 grams)	720 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	253 / 562	263 / 585
Shipping	273/607	283 / 629
Volume	1.09 CBM / 38.62 CBF	


Dimensions	Net (mm/in)	Shipping (mm/in)
Width	532/20.9	710 / 28.0
Depth	823 / 32.4	890/35.0
Height	1563 / 61.5	1730 / 68.1

Electrical	MFS	MCA	Power(kW)
220-240/50/3	20	16	4.4
208-230/60/3	30	20	4.4
208-230/60/1	40	30	4.4

• Above specifications are subject to change without notice

SPACEMAN USA

224 Commerce St. Unit A1, Broomfield, CO 80020 PHONE: +01 720-328-1020 FAX: +01 720-528-8113 Email: sales@spacemanusa.com www.spacemanusa.com



FEATURES	
Control Systems	Two, Digital
Refrigerated Hoppers	
Hopper Agitator	
Temperature Display	
Standby Mode	\checkmark
Auto Clsoing Dispensing Valves	
Dispensing Speed Control	\checkmark
Low Mix Indicator Light & Alarm	
Low Temperature Protection	\checkmark
Motor Overload Protection	
High Pressure Protection	\checkmark
Defrost & Quick Freeze	
Soft Start	\checkmark
Direct Drive Pump (A only)	

AVAILABLE OPTIONSWater CooledImage: Content of the second of the second