

6235B-C 6235AB-C

SOFT SERVE FREEZER

2 Flavor, Countertop, Pasteurization A: Pump Feed Model









Powerful & Versatile

two-flavor table model with

Auto-Pastuerization and

intelligent controls

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset scheduels

Ideal for medium capacity outlets to serve ice cream and gelato with desire for significant reduction in labor cost of cleaning.

Hopper Agitators

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- $\bullet \ \ \text{High pressure switch to prevent compressor overheating}$

Quick Refresh

Turn on freeze immediately to freeze down to serving viscosity when quick service is required after long idle period

Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






6235B-C/6235AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	2 + Twist
Freezing Cylinders	2 x 1.7L / 1.8qt
Mix Hoppers	$2 \times 8L (5L for A)$
Output Capacity (80 grams)	380 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb	Kg/lb (Pump)
Net	144 / 317	154 / 340
Shipping	160 / 353	170/375
Volume	0.48 CBM / 1a	6.95CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	444 / 17.5	530 / 20.9
Depth	705 / 27.8	850 / 33.5
Height	880 / 34.6	1070 / 42.1

Electrical	MFS	MCA	Power(kW)
220-240/50/1	25	16	2.4
208-230/60/1	30	18	4.1

 $\boldsymbol{\cdot}$ Above specifications are subject to change without notice

FEATURES	
Control Systems	Double, Digital
Refrigerated Hoppers	
Hopper Agitator	
Temperature Display	
Standby Mode	\checkmark
Auto Closing Dispensing Valves	
Dispensing Speed Control	\checkmark
Low Mix Indicator Light & Alarm	
Low Temperature Protection	\checkmark
Motor Overload Protection	
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	\checkmark
Auto-Pastuerization	

AVAILABLE OPTIONS	
Water Cooled	
Top Air Discharge Chute	
Cart (Trolley)	\checkmark