

# 6235B-C 6235AB-C

## **SOFT SERVE FREEZER**

2 Flavor, Countertop, Pasteurization A: Pump Feed Model









#### Powerful & Versatile

two-flavor table model with

### Auto-Pastuerization and

intelligent controls

#### **Auto-Pasteurization**

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

#### **Digital Control and Display**

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

#### **Operation Logging**

Logs every operation and error to provide history and data for easy troubleshooting

#### **Auto Programming**

Allows automatic switching of operation modes based on preset scheduels

Ideal for medium capacity outlets to serve ice cream and gelato with desire for significant reduction in labor cost of cleaning.

#### **Hopper Agitator**

Maintains product consistency and prevents product separation

#### **Defrost for Cleaning**

Increases efficiency during cleaning by heating frozen product in cylinder

#### **Safety Protections**

- · Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

#### **Quick Refresh**

Turn on freeze immediately to freeze down to serving viscosity when quick service is required after long idle period

#### **Self Closing Valve with Speed Control**


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






# 6235B-C/6235AB-C

# **SOFT SERVE FREEZER**





#### **SPECIFICATIONS**

Flavors	2 + Twist
Freezing Cylinders	2 x 1.7 L / 1.8 qt
Mix Hoppers	2 x 8 L (5L for A)
Output Capacity (80 g)	380 serves/hr
Clearance Requirements	152 mm/6" on back

Weight	Kg/lb(Gravity)	Kg/lb (Pump)
Net	141 / 311	157 / 346
Shipping	162 / 357	171 / 377

Dimensions	Net (mm/in)	Shipping (mm/in)	
Width	444 / 17.5	530 / 20.9	
Depth	735 / 28.9	950 / 37.4	
Height	906 / 35.7	1030 / 40.6	
Volume	0.52 CBM / 18.31 CBF		

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	3.6	17	25
208-230/60/1	3.8	18	25

	TI	ID	ES
г	۱,	ᇧ	EJ

Double, Digital
$\checkmark$
lacksquare
ightharpoons
$\overline{\mathbf{V}}$

#### **AVAILABLE OPTIONS**

Top Air Discharge Chute



· Above specifications are subject to change without notice