

# 6338-C/6338A-C

# **SOFT SERVE FREEZER**

Single Flavor, Floor, Digital Control A: Pump Feed Model









# Most Powerful and Versatile

1-flavor high capacity floor model for ice cream, frozen yogurt and much more

#### **Fast Freeze Down**

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

# **Digital Control and Display**

Digital control provides access to system settings and displays critical system information

## **Auto Programming**

Allows automatic switching of operation modes based on preset schedules

#### Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight

# **Hopper Agitator**

Maintain product consistency and prevent product separation

Ideal for high capacity outlets to serve ice cream, frozen yogurt, gelato or sorbet. Fully loaded with all standard options. Small footprint helps save floor space.

## **Soft System Start**

Slow motor start reduces equipment noise and stress on drive train

#### **Direct Drive Transmission**

Eliminates consumable moving parts and increases transmission efficiency

# **Safety Protections**

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

## **Defrost for Cleaning**

Increases efficiency during cleaning by heating frozen product in cylinder

# **Quick Freeze**

Turn on freeze immediately to freeze down to serving viscosity when quick service is required after long idle period

# **Self Closing Valve with Speed Control**


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






# 6338-C / 6338A-C

# **SOFT SERVE FREEZER**





## **SPECIFICATIONS**

Flavors	1
Freezing Cylinders	1 x 3.2L / 3.4qt
Mix Hoppers	1 x 15L (10L for A)
Output Capacity (80 grams)	400 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	173 / 381	185 / 408
Shipping	189/417	200 / 441
Volume	0.83 CBM / 29.31 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	444 / 17.5	550 / 21.7
Depth	680 / 26.8	900/35.4
Height	1549 / 61.0	1670 / 65.7

Electrical	MFS	MCA	Power(kW)
380-415/50/3	10	8	2.7
208-230/60/3	20	15	2.7

FEATURES	
Control System	Single, Digital
Refrigerated Hopper	
Hopper Agitator	$\checkmark$
Temperature Display	
Standby Mode	$\checkmark$
Auto Closing Dispensing Valve	ightharpoons
Dispensing Speed Control	$\checkmark$
Low Mix Indicator Light & Alarm	ightharpoons
Low Temperature Protection	$\checkmark$
Motor Overload Protection	
High Pressure Protection	$\checkmark$
Defrost & Quick Freeze	
Soft Start	$\checkmark$
Direct Drive Pump (A only)	lacksquare

AVAILABLE OPTIONS	
Water Cooled	
Top Air Discharge Chute	

<sup>·</sup> Above specifications are subject to change without notice