

6338AB-C

SOFT SERVE FREEZER

1 Flavor, Floor, Pump, Pasteurization









Most Powerful & Versatile High capacity 1-flavor floor model with Auto-Pasteurization and intelligent control

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critical info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset schedules

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato but with desire for significant reduction in labor cost of cleaning.

Hopper Agitators

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

Quick Refreeze

Turn on freeze immediately to freeze down to serving viscosity when quick service is required after long idle period

Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






6338AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	1
Freezing Cylinders	1 x 3.2 L / 3.4 q t
Mix Hoppers	1 x 10 L / 10.6qt
Output Capacity (80 grams)	400 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb
Net	188 / 414
Shipping	198 / 437
Volume	0.83 CBM / 29.31 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	444 / 17.5	550 / 21.7
Depth	785 / 32.0	900/35.4
Height	1549 / 61.0	1670 / 65.7

Electrical	MFS	MCA	Power (kW)
380-415/50/3	20	10	3.0
208-230/60/3	20	12	3.0
208-230/50/1	20	16	2.5
208-230/60/1	20	18	2.5

[·] Above specifications are subject to change without notice

FEATURES	
Control Systems	Sinqle, Digital
Refrigerated Hoppers	
Hopper Agitator	\checkmark
Temperature Display	
Standby Mode	\checkmark
Auto Clsoing Dispensing Valves	ightharpoons
Dispensing Speed Control	\checkmark
Low Mix Indicator Light & Alarm	
Low Temperature Protection	\checkmark
Motor Overload Protection	
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	\checkmark
Direct Drive Pump	
Auto-Pasteurization	\checkmark
AVAILABLE OPTIONS	

Water Cooled Top Air Discharge Chute