

6338B-C 6338AB-C

SOFT SERVE FREEZER

1 Flavor, Floor, Pasteurization A: Pump Feed Model









Most **Powerful** & **Versatile**High capacity 1-flavor floor model with **Auto-Pasteurization**and intelligent control

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critical info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset schedules

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato but with desire for significant reduction in labor cost of cleaning.

Hopper Agitator

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

Refresh and Revive

Restore perfect consistency automatically to reduce product waste and labor cost while ensuring food safety


Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control





6338B-C/6338AB-C SOFTSERVE FREEZER





SPECIFICATIONS

Flavors	1
Freezing Cylinders	1 x 3.2 L / 3.4 q t
Mix Hoppers	1 x 12L (10L for A)
Output Capacity (80 grams)	440 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	183 / 403	188 / 414
Shipping	193 / 425	198 / 437
Volume	0.75 CBM / 26.53 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	444 / 17.5	520 / 20.5
Depth	680 / 26.8	860 / 33.9
Height	1543 / 60.7	1680 / 66.1

Electrical	Power (kW)	Total Amps (A)	Fuse (A)	
380-415/50/3	2.9	9	16	
208-230/60/3	3.1	12	20	

FEATURES	
Control System	Single, Digital
Refrigerated Hopper	
Hopper Agitator	\checkmark
Temperature Display	
Standby Mode	\checkmark
Auto Closing Dispensing Valve	ightharpoons
Dispensing Speed Control	\checkmark
Low Mix Indicator Light & Alarm	
Low Temperature Protection	\checkmark
Motor Overload Protection	$\overline{\mathbf{V}}$
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	\checkmark
Direct Drive Pump	
Auto-Pasteurization	\checkmark
AVAILABLE OPTIONS	

· Above specifications are subject to change without notice

Water Cooled

Top Air Discharge Chute