

6368AB-C

SOFT SERVE FREEZER

Two Flavor, Floor, Auto-Pasteurization









Most Powerful & Versatile

Medium capacity 2-flavor floor model

with Auto-Pasteurization

and intelligent controls

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset scheduels

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato with desire for significant reduction in labor cost of cleaning.

Hopper Agitators

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections


- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- · High pressure switch to prevent compressor overheating






6368AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	2 + Twist
Freezing Cylinders	2 x 1.7L / 1.8qt
Mix Hoppers	2 x 10 L / 10.6qt
Output Capacity (80 grams)	600 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb
Net	250 / 556
Shipping	270 / 600
Volume	0.90 CBM / 28.85 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	532 / 21.7	660 / 23.6
Depth	766 / 30.2	830 / 32.7
Height	1494 / 58.8	1640 / 64.6

Electrical	MFS	MCA	Power(kW)
380-415/50/3	30	20	5.0
208-230/60/3	40	30	5.0

FEATURES	
Control Systems	Two, Digital
Refrigerated Hoppers	
Hopper Agitator	\checkmark
Temperature Display	
Standby Mode	\checkmark
Auto Clsoing Dispensing Valves	lacksquare
Dispensing Speed Control	\checkmark
Low Mix Indicator Light & Alarm	lacksquare
Low Temperature Protection	\checkmark
Motor Overload Protection	
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	\checkmark
Direct Drive Pump	
Auto-Pasteurization	\checkmark

AVAILABLE OPTIONS	
Water Cooled	$\overline{\mathbf{v}}$
Top Air Discharge Chute	

[·] Above specifications are subject to change without notice