

# 6455-C

### FROZEN BEVERAGE FREEZER

Two flavor, Countertop, Gravity feed









## Most Compact & Versatile

Two flavor countertop model for frozen beverage and smoothies

#### **Fast Freeze Down**

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

#### Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

#### Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

#### See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

#### Standby & Indicator

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator light turns ON blue under Standby mode

Perfect solution for alcoholic and non-alcoholic frozen beverages in bars, restaurants, hospitals, schools and kiosks

#### **Hopper Agitators**

Maintain product consistency and prevent product separation

#### **Self-closing Dispensing Valves**

Automatically prevents product overflow after dispense

#### **Safety Protections**

- $\bullet \ \ \mathsf{High}\,\mathsf{pressure}\,\mathsf{switch}\,\mathsf{to}\,\mathsf{prevent}\,\mathsf{compressor}\,\mathsf{overheating}$
- Thermal overload to protect from motor overheating

#### **Light Box (Optional)**

- Illuminates flavor cards to attract more business
- Changes color to indicate Low Mix and Standby

#### **One-hand Operated Spinner (Optional)**


- Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time






## 6455-C

## FROZEN BEVERAGE FREEZER





#### **SPECIFICATIONS**

Flavors	2
Freezing Cylinders	2 x 3.8L / 4.0qt
Mix Hoppers	2 x 8.0L / 8.5qt
Output Capacity (250ml)	112 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb	
Net	146 / 322	
Shipping	166 / 366	
Volume	0.45 CBM / 16.01 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	476 / 18.7	520 / 20.5
Depth	651 / 25.6	800 / 31.5
Height	972 / 38.3	1090 / 42.9

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	2.3	12	16
208-230/60/1	2.3	12	15

FEATURES	
Control Systems	Two, Mechanical
Refrigerated Hoppers	
Hopper Agitators	$\checkmark$
Auto Closing Dispensing Valves	
Low Mix Indicator Light	$\checkmark$
Low Mix Indicator Alarm	
Standby Mode	$\checkmark$
Standby Indicator Light	
High Pressure Protection	$\checkmark$
Thermal Overload Protection	

## AVAILABLE OPTIONS

Top Air Discharge Chute	$\checkmark$
Spinner	$\checkmark$
Light Box	<b>~</b>

· Above specifications are subject to change without notice